	Poly Microphones support overview Wife: \$4580000 Mand: \$\sigma\$ Second \$\frac{\text{#}}{2}\$ Usuages \$\frac{\text{U}}{2}\$ Usuages																																	
Valid on : Foly Studio X/67500 Smrware version :	03/04/2023	Lecend : V	Supported	* Unsuggerted	Unsupp	ported but part	Sally works - fo	or lab environme	nt only! Use at you	er own risk III	₹ Roads	nap feature																						
Please note : All info is subject to change without notice! This is not official Poly document!				=	_					w w	1			•	400				•											Y	7	1		
Poly Davice			Poly Studio PS	is Paly Stu	dio Riiti Po	aly Studio USB	Poly Studio X30	Poly Studio X3	Poly Studio X30	Poly Studio X30	Poly Studio X30	Poly Studio XSO	Poly Studio XS0	Poly Studio XSO	Poly Studio XSC	Paly Studio XSO	Poly Studio X70	Poly Studio X70	Poly Studio X70	Paly Studio X71	Poly Studio X70	Poly G7500	Paly G7500	Poly G7500	Paly 67500	Poly G7500	Poly MTRoW PC	Poly 2RoW PC	Pary Trie 8100/8800	Poly Trio C60	timitations	Notes		
Build-in microphone pick-up range [m]			àm	4.6	im.	4.6m	> make	664	4.60	-	C	D poly	ų,	7.6m	-	a :	D- poly	Tii i	7.6m	-	a	> poly	m2.5	70.000	-	(27)	Tili .	70000	6.1m	6.1m				
UC App provider			8100	80		8900	poly	MS Teams from	ZOOM 200m Rooms		Permanent Device			ZOOM Rooms	Goods Marr	Permanent Device			ZOOM Jaam Rooms	Goods Marr	Permanent Device		MS Teams Brown	ZOOM Zoom Rooms	Goods Meet	Permanent Device	Mi Teams Room	ZOOM Zeen Rooms	All modes	All modes				
Microphone Picture Skil (EMEA) Connection Pick-Up radius [re]				-		-				_						_												-						
Rivild in microphones	0		internally connected		~	~		/	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	×	×	*	N/A	×	×	×	~	~	Earling shalin . supported only in modes i VIR Optimized, SAR, Generic hedita [SAR] Home Controller You wan't paint or Adaptation a Poly No. OD is patern with Poly No. BEES or BEES scalarses, as also a Poly No. OE control controller of source analysis of one W. E.	
Poly Expansion Microphone (Debut)	4	0-69631-001	Ri-11 (direct		*	×	:	/	×	×	×	×	×	~	~	~	~	~	~	~	~	~	~	×	×	×	N/A	×	×	×	×	×	Studio XSO: Trio and XSO Expansion microphone can't be use together.	7.6m long cable available in the package, Possible Cat5 extension kit for cables up to 38m (2215-88019-801)
Poly IP Table Microphone			J-45 JP Network		*	*	:	×				×					×					×		~	~	~	N/A	~	×	×	×	×		More than 3 IP microphones or active switch connected to IP mic port on
Poly IP Celling Microphone		WLSCTCL/WH	-45 (P Network	3 En.	×	*	:	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	~	~	~	N/A	~	×	×	×	×		G7000 ren ha used at unor num risk only (II) More than A IP microphones or active switch connected to IP mic port on
Array	221	15-85360-001	Connection) 5-45 (P Network	3.6m	×	*		×	~	~	~	×	~	~	~	~	×	~	~	~	~	×	~	Us to Finds	Unto Tenica	United States	N/A	Us to Free	~	~	~	×	Date 100 To 100	G7500 can be used at your own risk only III Trio can be used with Trio Supansion microphones. When you pair a fine 8500, Trio 8800, or Trio C60 system, Device Mode
Trio 8500	220	00-66700-025	Connection)	6.2m	*	*	2	*	/	/	/	*	/	~	/	/	*	~	~	~	~	*	~	~	~	~	N/A	/	~	~	~	*	toeether.	works only in Poly Video Mode. Trio can be used with Trio Supersion microphones.
Trio 8800	7.200	0-66070-001		6.tm	•	-		**	and the same	er coman	*		Date of the large of	Calcuratoria 112	Day damand	Dendmani		lav non are.)	linconnect)	Dan danami	Dan more and		Standard State	Dandarani	Carpterand	Decemenary)	80/76	Decrees	nin data and	Discolatora D	7		Studio XSO: Trio and XSO Sugarsion microphone can't be use soaether.	When you pair a Trio 8500, Trio 8800, or Trio 550 system, Device Mode works only in Poly Video Mode.
Expansion Microphone Kit for Trin GCN1/9800 (700x)		VI.60790.40H	Ri-9 (direct	£ tim (medicid)	•	-	•	*	•	**	**	•	***	***	•	•••	•	•	**	**	**	•	**	**	•	**	30y 30	•	•	•		•	2 to loss rubbs	
Trio CSO (Reams SKU)	Y	00-86580-019	1-45 (P Network Connection)	6.1m	*	*	•	×	~	~	~	*	~	~	~	~	×	~	~	~	~	×	~	~	~	~	N/A	~	~	~	*	~	Studio XSO: Trio and XSO Sugansion microphone can't be use soaether.	Trio can be used with Trio Expansion microphones. When you pair a Trio 8500, Trio 8800, or Trio C60 system, Device Mode works colv in Polv Video Mode.
	-	00-86430-001	Ri-9 (direct connection)	6.1m (ordeid)	*	×	•	×	*	×	*	×	×	*	×	*	×	*	*	×	×	×	×	×	*	×	N/A	×	×	×	*	~	2.5m ione cables (solid)	
Poly Sens 10		219654-01	USB-A		*	*	:	×				×				8	×	8				×					N/A	R			×	×	Sunc 20 is not certified or supported as peripherals for MTRoW	Various SkUs available ISSBA. USBC. MSFT version
Broke George 205		217029-01	200		*	*	:	×				×	TIP A	III A		9	×					×	TI A				N/A				×	*	Cont 10 is not partitled or supported to particular as the political control of the partitled or supported to particular as the political control of the partitled or supported to particular as the particular as	
			BTGGG USB-A Wireless BT		×	*	:	×				×		THE A			×					×	1				N/A				×	×		
Polu Svec 20+	_	216865-01	donele	2m	×	*	:	×				×					×					×					N/A		~		×	×	Sinc 20 is not certified or supported as peripherals for MTRoW MTR certification is for single Sync 40 connected via USB cable	Various Skits available (USB-A, USB-C, MSFT version)
Polis Sens. 60		216874-01		2.5m	×	*	:	×				×					×					×					N/A		10	~	×	×	only! MTR certification is for single Sync 60 connected via USB cable	Various Situs available (Senc 60+ with 9T600, MSFT version)
Poly Sens 60	22	216872-01	USB-A / USB-C	ln.	×	*		×	~	~	~	×	V	V	~	~	×	1	~	~	~	×	~	~	~	~	N/A	~	×	×	~	~	only! Studio X/G7500 : When connected, you can control your headset audio but not the system audio jusch as mute or volume.	Various Stitu available (MSFT version)
Only Standard		Manage Cirilia	G robin	N/A	- 74	-		**		-	-	174	-		-	-	-	-	-	-	-		1	-	-	-		-			in service and		manu ann ma cre spiserr aidio (tach at mase or volume	
Shure IntelliMix P200	1 2 ,	Shure SKU	USB-A	N/A	*	*	•	*	*	×	*	×	*	~	~	~	-	~	~	~	~		~	~	~	~	N/A	~	~	~	*	*		Once connected to the system, the processor handles all audio. You can't use speakers and microphones that aren't connected to the processor. The video system automatically disables its internal echo cancellation processine.
QSC Core Series audio processors		osc sku	USB-A	N/A	*	*	•	×	*	*	×	*	*	~	~	~		~	~	~	~	Щ	~	~	~	~	N/A	~	~	~	*	×		Once connected to the system, the processor handles all audio. You can't use speakers and microphones that aren't connected to the processor. The video extern automatically disables its internal echo cancellation processins.
Stamp 05P USB audio 000085003		Riamo SKU	USR-A	N/A	×	*	!	×	×	×	×	×	*	~	~	~		~	~	~	~		~	~	~	~	N/A	~	~	~	*	*		Once connected to the system, the processor handles all audio. You can't use speakers and microphones that aren't connected to the processor. The video system automatically disables its internal echo cancellation processins.
2.5 mm Audio Input for external microphones / 059	D		3.5mm jack	N/A	*	*	!	*	*	*	*	*	*	Control Andre Coly	*	Control Andre Coly	*	Control Audio Coly	Committee Con	*	Committee Co.	*	Control Safe Con	~	~	~	N/A	~	*	*	*	*	Studio XSO - 3.5 mm input doesn't support ASC	MRRaW - 2.5mm input is not intended for external audio DSPI Supported for use with a simple headset for hearing-impained use-cases Studio LISE - 1,5mm input is for external audio source (such as TV, Amplifier or Phone) to use the device as a sound bar when not in video call!